

Item#	Description	Box Qty.	Less Box Qty.	Box Qty.
-------	-------------	----------	---------------	----------

### SANDING DISCS

PF62533 **5" Quick Change Alum. Oxide** 25



Aluminum Oxide A sanding disc with quick-change hub, 5" diameter, 5/8-11 thread, 36 grit, 12,200 max. RPM. For general-purpose grinding.

PF62543 **5" Quick Change Alum. Zirconia** 25



Zirconia Alumina Z sanding disc with quick-change hub. 5" diameter, 5/8-11 thread, 36 grit, 12,200 max. RPM. Designed for coarse grinding and high stock removal, with an extended service life. Zirconia alumina is a high-performance abrasive which delivers best results on high-powered angle grinders at increased contact pressure.

PF69525 **5" Ribbed Backing Pads** 25



Ribbed rubber backing pad for sanding discs. 5" diameter, 5/8-11 thread size, regular backing density, 10,000 max. RPM. Ribbed design allows for better cooling, which improves disc life.

### GRINDING WHEELS



PF61001 **4 1/2" x 1/4"; 5/8"-11, 24 Grit, Type 27** 10

Aluminum Oxide grinding wheel for steel and cast iron. 4-1/2" diameter, 1/4" thickness, 5/8-11 thread, 24 grit, 13,300 max. RPM. General purpose grinding wheel for use on all metals. Smooth grinding action and fast removal rates with minimal contact pressure. Manufactured without addition of ferrous, sulphurous or chlorinated fillers. For surface grinding and edge grinding. Use with angle grinders of all power output levels.

PF61008 **5" x 1/4"; 5/8"-11, 24 Grit, Type 27** 10

Aluminum Oxide grinding wheel for steel and cast iron. 5" diameter, 1/4" thickness, 5/8-11 thread, 24 grit, 12,200 max. RPM.

PF61006 **7" x 1/4"; 5/8"-11, 24 Grit, Type 27** 10

Aluminum Oxide grinding wheel for steel and cast iron. 7" diameter, 1/4" thickness, 5/8-11 thread, 24 grit, 8,600 max. RPM.

Item#	Description	Box Qty.	Less Box Qty.	Box Qty.
-------	-------------	----------	---------------	----------

### CUT-OFF WHEELS

PF63115      **4 1/2" x 1/8", 5/8-11, Type 27**

10

Aluminum Oxide cut-off wheel for steel and cast iron, Type 27 (depressed center). 4-1/2" diameter, 1/8" thickness, 5/8-11 thread, 46 grit, 13,300 max. RPM. Use for cutting of sheet metal, sections, and solid material. 1/8" thickness for maximum tool life with high lateral stability. Use with angle grinders of all power output levels.



PF63842      **7" x 1/8", 5/8" AH, Type I**

25

Aluminum Oxide cut-off wheel for steel, Type 1 (flat). 7" diameter, 1/8" thickness, diamond 5/8-1/2 arbor hole, 24 grit, 8,600 max. RPM. Performance cut-off wheels with diamond-shaped bore for use with circular saws. Includes 5/8" and 1/2" adapters for use on angle grinders and straight shaft grinders. For cutting of sheet metal, sections, and solid material.



PF64502      **14" x 3/32" Chop Saw Wheel, 1" AH**

10

Aluminum Oxide cut-off wheel for steel. 14" diameter, 3/32" thickness, 1" arbor hole, 36 grit, 4,400 max. RPM. Multipurpose tool for abrasive cutting operations using stationary machines. Aggressive abrasive performance for fast cuts and very long tool life. For cutting of sections and solid material, rebar, tubing, and other small cross sections. Use with up to 5 horsepower output machines.



### SPECIALTY

PF63340      **5" x 1/8" Duo Disc, 5/8-11, 46 Grit**

10

GRINDING AND CUTTING WITH THE SAME DISC  
DUODISC® combination cutting & grinding disc. 5" diameter, 1/8" thickness, 5/8-11 thread, 12,200 max. RPM. DUODISC® combination cutting, light deburring and surface grinding wheels conform to U.S. and international safety standards. 1/8" thickness for maximum tool life and high lateral stability. Manufactured without addition of ferrous, sulphurous or chlorinated fillers. Long service life and fast cutting action with angle grinders of all power outputs.



### HAND TOOLS

PF85033      **Wire Brush, Shoe Handle**

12

Shoe handle wire brush without scraper. 4 x 16 wire rows, 5" brush part length, carbon steel wire filament, 10-1/4" x 1-1/8" block, 1-3/16" trim length. PFERD Advance Brush premium hardwood scratch brush blocks are kiln-dried to keep wire tufts firmly in place, and hand-selected to ensure straightness and quality. Shoe handle scratch brushes provide good leverage, allowing a more powerful brush stroke than can be achieved with a curved handle brush.



PF85034      **Wire Brush with Scraper**

12

Shoe handle wire brush with scraper. Same as PF85033, but includes 1-7/16" steel scraper attachment.

8530 UNSWORTH AVE. SACRAMENTO, CA 95828-1009 1-916-381-4065	13111 DAHLIA ST. FONTANA, CA 92337-6902 1-909-350-9040	8937 SAN FERNANDO RD. SUN VALLEY, CA 91352-1410 1-818-504-3700	1265 N. CUYAMACA ST. EL CAJON, CA 92020-1549 1-619-449-0333	10010 PORTLAND AVE. TACOMA, WA 98445-3956 1-253-535-5500
---	--	--	---	--